



The ORiNOCO 11a/b/g ComboCard gives you the flexibility to connect to any 802.11 wireless network, via a single, convenient card. Just plug the 11a/b/g ComboCard into the Cardbus slot of your notebook computer and you have everything you need for maximum wireless productivity in an enterprise, public building or at home. The 11a/b/g ComboCard is part of ORiNOCO's family of client and infrastructure products – everything you need to work anytime, anywhere and the way you want.

ORINOCO® 11a/b/g Combocard

Simple, convenient and secure Wireless LAN connectivity for every network

Proxim's ORiNOCO ComboCard delivers the utmost in mobile convenience and performance, allowing secure connections to 802.11b, 802.11a and 802.11g networks from a single card. With the ORiNOCO ComboCard, you can move easily between 802.11 networks at work, home, and in public spaces. The ComboCard provides wireless networking data rates of up to 54 Mbps in 802.11 mode and 108 Mbps in Proxim's 2X mode. The ComboCard provides throughput five to ten times higher than 802.11b-only products and supports bandwidth-intensive applications.


Fully compliant with all 802.11 standards, the ComboCard delivers proven high-performance for a broad range of applications and host computer systems. The 11a/b/g ComboCard protects your network investment by allowing you to deploy and simultaneously support new higher speed 802.11a and g infrastructure within legacy 802.11b networks. The ORINOCO ComboCard provides multiple security levels, with encryption up to 152-bit WEP and 802.1x authentication for enterprise-class security. The ComboCard is shipped hardware-ready for upgrade to Wi-Fi Protected Access (WPA) security. Available in Gold and Silver versions, the ComboCards include an easy-to-use utility for quick, simple connection.

APPLICATIONS

- Small/medium business, enterprises: improved productivity with mobile network, Internet, and email inside buildings, around campus
- Universities: flexible, immediate, mobile faculty and student connectivity in dorms, classrooms, offices
- Quick network build-out for new employees
- Hospital-wide transmission of bandwidthintensive medical data and image files

FEATURES

- Plugs directly into CardBus Type-II slot
- Intuitive client utility for easy, fast configuration
- Unlimited number of location profiles (Gold only)
- Seamless roaming between 802.11a/b/g networks
- Enterprise-class 802.1x security and multilevel WEP encryption
- Transmitter power control for optimal performance (Gold only)





About Proxim

Proxim Corporation is a leading manufacturer of high-performance wireless local area networking (WLAN) and wireless wide area networking (WWAN) products. Proxim's ORiNOCO line of products encompasses a full range of indoor and outdoor WLAN products, as well as enhanced security products for public areas and security-conscious enterprises. Proxim sells its ORiNOCO products and solutions to service providers, enterprise customers and endusers via a network of leading OEM partners, a vast array of value-added resellers, and several e-commerce sites.

ORiNOCO 11a/b/g ComboCard Specifications

INTERFACE		
CardBus Card (32-bit) Type II PC Card	I	
RADIO CHARACTERISITICS		
Frequency	FCC (26 Channels) 2400-2484; 5150-5250; 5250-5350; 5725-5850 MHz ETSI (32 Channels) 2400-2484; 5150-5250; 5250-5350; 5470-5720 MHz TELEC (18 Channels) 2400-2484; 5150-5250 MHz IDA (22 Channels) 2400-2484; 5150-5250; 5725-5850 MHz	
Modulation Techniques	802.11a, 802.11g Orthogonal Frequency Division Modulation (64 QAM, 16 QAM, QPSK, BPSK) 802.11b Direct Sequence Spread Spectrum (CCK, DQPSK, DBPSK)	
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK	
Maximum Output Power	802.11a, 802.11g: 60 mW EIRP 802.11b: 85 mW EIRP	
Data Speeds (Automatic fallback for extended range)	802.11a, 802.11g modes: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11b mode: 11, 5.5, 2, 1 Mbps 2X mode: 108, 96, 72, 48, 36, 24, 18, 12 Mbps	
Power Consumption	802.11a: Tx – 520 mA, Rx – 310 mA 802.11b, 802.11g: Tx – 600 mA, Rx – 330 mA	
PHYSICAL SPECIFICATIONS		
Dimensions	121.75 mm X 54.00 mm X 5 mm (PC Card)	
Weight	55 grams	
ENVIRONMENTAL SPECIFICATIONS		
	Temperature (Ambient)	Humidity
Operating	0 to 55° C	90% (non-condensing)
Storage	-10 to 75° C	95% (non-condensing)
PC CARD SPECIFICATIONS		
Type II CardBus	32-bit interface	
Power Supply Voltage	3.3 VDC from host (+/-0.2V)	
LEDS		
2 LEDs:	Power Network Activity	
OPERATING SYSTEMS		
Windows 98 SE, 2000, Me, XP		
SECURITY		
802.1x support	EAP – TLS, TTLS, MD5, PEAP, LEAP	
Gold	152/128/64-bit WEP for 802.11a, 128/64-bit WEP for 802.11b/g	
Silver	128/64-bit WEP	
WARRANTY		
3 years		
PACKAGE CONTENTS		
CardBus CardGetting Started GuideCD-ROM with drivers, installation a	nd configuration utility.	
Ordering information	<u></u>	

ORDERING INFORMATION	
8480	ORiNOCO 11a/b/g ComboCard Gold
8481	ORiNOCO 11a/b/g ComboCard Silver

RELATED PRODUCTS

AP-600a, AP-600b, AP-600g

AP-2000, AP-2500

ORINOCO 11b PC Card, 11b USB Adapter, 11b PCI Adapter, 11b Ethernet Adapater

Proxim Corporation tel: 800.229.1630 935 Stewart Drive tel: 408.731.2700 Sunnyvale, California 94085 fax: 408.731.3675

Wi-Fi is a trademark of the Wi-Fi Alliance. Windows and Windows Me are registered trademarks of Microsoft Corporation.





